The attached Appendix includes marked-up copies of each rewritten claim

(37 C.F.R. 1.121(c)(1)(ii)).

Respectfully submitted,

James A. Oliff

Registration No. 27,075

Eric D. Morehouse

Registration No. 38,565

JAO:EDM/gam

Date: July 24, 2001

OLIFF & BERRIDGE, PLC P.O. Box 19928 Alexandria, Virginia 22320 Telephone: (703) 836-6400 DEPOSIT ACCOUNT USE AUTHORIZATION Please grant any extension

necessary for entry; Charge any fee due to our Deposit Account No. 15-0461



7

The following are marked-up versions of the amended claims:

- 4. (Amended) A display device as claimed in claim 2-or 3, characterized in that said converting section pulse-width-modulates the value based on the image signal to convert the value into the analog signal.
- 5. (Amended) A display device as claimed in claim 2-or 3, characterized in that said converting section converts the value based on the image signal into the analog signal modulated to a pulse width based on a γ-characteristic.
- 6. (Amended) A display device as claimed in claim 2-or 3, characterized in that said converting section performs conversion into the analog signal at a constant period interval.
- 13. (Amended) A display device as claimed in claim 2-or 3, characterized in that said display control section controls light emission of current-driven luminescent devices in connection on the basis of the analog signal in place of performing tonal control using a liquid crystal, thereby effecting tonal control.
- 15. (Amended) A display device as claimed in claim 13-or-14, characterized in that said current-driven luminescent devices are structured by EL devices.
- 16. (Amended) A display device as claimed in claim 13-or 14, characterized in that said current-driven luminescent devices are structured by organic EL devices.
- 18. (Amended) A display device as claimed in any of claims 2, 3, 14 and 17, characterized by further laying a plurality of read lines correspondingly to said dot array pattern so that, if a read signal is transmitted, the image signals stored in said storing circuits are read out of said storing section.

Docket No. 109098

3

- 22. <u>(Amended)</u> A display device as claimed in claim 19-or 20, characterized in that said word line driver section and said row decoder section are allocated correspondingly to a length of said display drive section in a column direction, and said column decoder section and said column selection switch section are allocated correspondingly to a length of said display drive section in a row direction.
- 24. (Amended) A display device as claimed in claim 19-or 20, characterized in that said row decoder section selects a row for transmitting the write signal on the basis of an address signal representing a storage position.